



4x4 Polyester polymer concrete catch basin





Grate



- Grate is classified as 'Heavy Duty' and meets the requirements of AASHTO M306*.
- Grate provides 41% open area - 1,087 sq. in.

*AASHTO M306 requires that castings bear a minimum of 40,000 pounds on a 9" x 9" area. This represents a 2.5 safety factor over the 16,000 pound requirement of H20 and HS20. This load designation is appropriate for general traffic applications. Loading criteria is 40,000 — 100,000 pounds.

Base



ACO Specification Information

ACO DRAIN

4x4 Polyester polymer concrete catch basin

Description	Part No.	Invert Depth		Weight lbs.
		inches	mm	
4x4 Catch Basin - Polyester polymer concrete	05714	49.88	1267	808.0
Grey iron frame & 2-part slot grate	05978	-	-	1220.0

Part I - General	Part II - Product	Part III - Installation
<p>1.1 Related Work - Work specified in other sections includes but is not limited to: Excavation and backfill, cast-in-place concrete, and mechanical equipment.</p> <p>1.2 System Description - 4 x 4 Catch basin manufactured from polyester polymer concrete, complete with gray iron slotted grate.</p> <p>1.3 Submittals - Manufacturer will submit, when required, shop drawings showing schematic plan of total drainage system listing all parts being provided with exact center-line dimensions suitable for installation. Copies of the manufacturer's recommended method of installation shall be submitted for review.</p> <p>1.4 Project History - Manufacturer shall submit a list of installed projects, if required.</p> <p>1.5 Warranty - ACO provides a limited product warranty of one year based on installation according to manufacturer's installation instruction data.</p>	<p>2.1 Products - Manufacturer shall be ACO Polymer Products, Inc.</p> <p>2.2 Physical & Mechanical Characteristics</p> <ul style="list-style-type: none"> • Overall width - 51.38 inches (1305mm) • Overall length - 51.38 inches (1305mm) • Overall depth - 50.63 inches (1286mm) • Invert depth - 49.88 inches (1267mm) • Compressive strength - 14,000 psi • Flexural strength - 4,000 psi • Water absorption rate - <0.1% by weight <p>2.3 Box Profile - Pre-cast units with minimum wall thickness of 0.75" (19mm).</p> <p>2.4 Grates - Grates are slotted gray iron and are supplied as 2-part units. After removal of grates there shall be uninterrupted access to the catch basin to aid maintenance.</p>	<p>3.1 Excavation - Identify area for install. If trafficked by vehicles, a full concrete encasement is required. Excavate area large enough to fit catch basin plus a minimum of 10" of concrete on all four sides and base. Engineering advice should be sought as ground conditions may require additional concrete support.</p> <p>3.2 Outlet Connections - Openings for pipe connection can be positioned where required.</p> <p>3.3 Connection of channels: Catch basin can be used within a channel run. Remove sidewall to suit channel profile.</p> <p>3.4 Back Fill - Haunch around catch basin & backfill with concrete of 4,000 psi minimum strength. Finish concrete to 1/8" above required grate height.</p> <p>3.5 Install in strict accordance with manufacturer's recommendations & drawings. Details available at www.ACODrain.us.</p>

ACO Polymer Products, Inc.

Northeast Sales Office
P.O. Box 245
Chardon, OH 44024
Tel: (440) 285-7000
Toll free: (800) 543-4764
Fax: (440) 285-7005

West Sales Office
P.O. Box 12067
Casa Grande, AZ 85130
Tel: (520) 421-9988
Toll Free: (888) 490-9552
Fax: (520) 421-9899

Southeast Sales Office
4211 Pleasant Road
Fort Mill, SC 29708
Toll free: (800) 543-4764
Fax: (803) 802-1063



Electronic Contact:
info@ACODrain.us
www.ACODrain.us



© February 11, 2013 ACO Polymer Products, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our product since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO Polymer Products Inc. reserves the right to change the product and specifications without notice.